An ISO 9001: 2008 Certified



## **Aluminium Violet AGN**

(Technical Data Sheet)

Aluminium Violet AGN is a brilliant Violet dye in powder form and gives fast striking blue shade on aluminum, which is distinguished by outstanding fastness to light, weather and heat. This dye can be used for thinner .Due to high concentration of dye the consumption is much lower cost. This product assures uniform level dyeing on anodized aluminum and gives good fastness.

## **Chemical Properties:**

Physical Form : Dry Powder

Appearance : Dark Violet Powder
Chemical Class : Metalized azo dye.
Solubility :> 60 g/l @ 60 C<sup>0</sup>

Light Fatness : excellent Heat Fastness : excellent

## **Anodizing Recommendation:**

Coating Thickness : 10-25 microns
Concentration : 8-10 grams/l
Temperatures : 55 - 60 C
pH : 5.5 +- 0.5

Buffer : The bath must be buffered with

8 g/l sodium acetate tri hydrate 0.4 ml/l acetic acid for pH 5.5

Time : 5-10 Minutes.

Water Quality : Preferably de-ionized. Dyeing is also possible in tap water,

but this can reduce the service life of dye bath

**Sealing Methods:** Hot sealing is preferred.

**Disposal of spent dye bath.** Spent dye bath must be disposed of as per local law.

## Note:

The information above is believed to be accurate and represent the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information and we assume no liability resulting from its use. User should make their investigations to determine the suitability of the information for their particular purposes. In no event shall company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect incidental, consequential or exemplary damages.